EX PARTE OR LATE FILED

Duane Morris*

FIRM and AFFILIATE OFFICES

NEW YORK
LONDON
SINGAPORE

LOS ANGELES
CHICAGO
HOUSTON

HANOI

PHILADELPHIA SAN DIEGO

SAN FRANCISCO BALTIMORE

BOSTON

WASHINGTON, DC

LAS VEGAS

ATLANTA MIAMI

PITTSBURGH NEWARK

BOCA RATON

WILMINGTON PRINCETON

LAKE TAHOE
HO CHI MINH CITY

FILED/ACCEPTED

Federal Communications Commission
Office of the Secretary

MAY 13 2008

PERSONAL FAX: 202.478.2160 E-MAIL: kkeane@duanemorris.com

DIRECT DIAL: 202.776.5243

www.duanemorris.com

WILLIAM K. KEANE

May 13, 2008

Ms. Marlene H. Dortch Secretary Federal Communications Commission 445 12th Street S.W. Washington DC 20554

ORIGINAL

Re:

WT Docket No. 07-293; ID Docket No. 95-91;

GEN Docket No. 90-357: RM-8610

Ex Parte Statement

Dear Ms. Dortch:

This is to report that yesterday Oakley Brooks, Bombardier Inc.; Audrey Allison, the Boeing Company; Daniel G. Jablonski, Johns Hopkins University Applied Physics Laboratory; and the undersigned, counsel for Aerospace and Flight Test Radio Coordinating Counsel ("AFTRCC"), met with Helen Domenici, Chief, International Bureau; Julius P. Knapp, Chief, Office of Engineering and Technology; Roderick K. Porter, Deputy Bureau Chief, International Bureau; Joel Taubenblatt, Acting Deputy Bureau Chief, Wireless Telecommunications Bureau; Thomas Derenge, Deputy Chief, Mobility Division, Wireless Telecommunications Bureau; Ira Keltz, Deputy Chief, Office of Engineering and Technology; and Robert Nelson, Chief, Satellite Division, International Bureau, regarding AFTRCC's position in the above-referenced proceedings. Representatives of Sirius Satellite Radio Inc. and XM Radio Inc. were also in attendance. The points made by AFTRCC during the course of the meeting are reflected in its earlier filings in the dockets. In addition, a copy of the document attached hereto was distributed to attendees.

A copy of this ex parte notification is being filed electronically for inclusion in the referenced dockets.

Sincerely,

No. of Copies rec'd____

ListABCDE

William K. Keane

Counsel for Aerospace and Flight Test Radio Coordinating Council

DUANE MORRIS LLP

Duane Morris

Ms. Marlene H. Dortch May 13, 2008 Page 2

cc:

Helen Domenici

Julius P. Knapp

Roderick K. Porter

Joel Taubenblatt

Thomas Derenge

Ira Keltz

Robert Nelson

Oakley Brooks

Audrey Allison

Dan Jablonski

Paul Sinderbrand

Mary O'Connor

Doug Duet

David Urban

L'... O'C

Jim O'Connor

Kurt Schaubach

Jennifer McCarthy

Rajendra Singh

Ron Olexa

Jim Blitz

Ruth Ziegler

Terry Smith

Alan Pate

Craig Wadin

Robert Pettit

Doug Ayerst

Peter Rohrbach

Mike Lewis

Carl Frank

Scott Harris

David Don

Henry Hultquist


For Decades ViaSat has been a leading supplier of high quality tracking antennas to the telemetry users of the world. Using our experience we have refined our products into simple, robust, and technically superior telemetry systems.


The Patented ESCAN tracking feed provides low sidelobes, high scanning rates, and superior multi-path resistance. We also produce conical scan and single channel monopulse tracking feeds to fit a wide range of requirements.


The series 13000 pedestal features patented bearing technology that combines long trouble free life with ease of service and maintenance. Pulse Width Modulated (PWM) servo power amplifiers are matched with brushless DC servo motors to assure long trouble free operation. These pedestals are in service around the world, some in extreme harsh environments providing daily service.

The heart of the control system is ViaSat's 3880 Antenna Control Unit (ACU). The 3880 is ViaSat's fourth generation ACU and provides unequalled performance for tracking systems. The 3880 provides for control, testing, and mission monitor (track files), far better than any previous control unit.

Telemetry Systems are available in fixed and mobile configurations as well as many size offerings (in addition to those listed here).







L- AND S-BAND RANGE TELEMETRY EVETE AT-A--CHANC

- * A leading source for more than 40 years
- Highly multi-path resistant ESCAN feed
- High dynamics, high accuracy tracking pedestal
- Fourth generation touch screen antenna control unit
- Mobil e and fixed configurations
- Remote control

SPECIFICATIONS AND STANDARD ANTENNA SELL

Frequency 1	1.8m 1435 – 2300 MHz	2.4m 1435 – 2300 MHz	3.0 m 1435 – 2300 MHz	3.6m 1435 – 2300 MHz
Gain	28.5 dB @ 2300 MHz	31.0 dB @ 2300 MHz	33.0 dB @ 2300 MHz	35.0 dBi @ 2300 MHz
HPBW @ 2300 MHz	5.1° @ 2300 MHz	3.8° @ 2300 MHz	3.0° @ 2300 MHz	2.5° @ 2300 MHz
First Side Lobes	16 dB Below Peak	18 dB Below Peak	18 dB Below Peak	20 dB Balow Peak
Polarization	LHC & RHC Sim	LHC & RHC Sim	LHC & RHC Sim	LHC & RHC Sim
Axial Ratio	2.0 dB Max at beam peak	2.0 dB Max at beam peak	2.0 dB Max at beam peak	2.0 dB Max at beam peak
Guaranteed G/T 2 & 3	5.8 dB/K @ 2300 MHz	8.6 dB/K @ 2300 MHz	10.5 dB/K @ 2300 MHz	12.1 dB/K @ 2300 MHz

DYNAMICS

Velocity 30° sec

Acceleration 30° per sec²

Azimuth Travel +/- 375°

Elevation Travel -10° to +110°

ENVIRONMENTAL

Temperature -30° to +70° C

Rain Up to 5 inches per hour

Ice 0.5 inch Radial

Wind Operate in 45 MPH, Stow in 120 MPH

Voltage/Frequency 120/208 VAC 50/60 Hz

OPTIONS

- · Separate data and tracking channels for improved performance
- Dual drive pedestal
- · Slip-rings and rotary joint for continuous azimuth rotation
- Transmit versions available in all frequency bands
- Video camera
- Alignment telescope
- Acquisition antenna
- Dual or selectable polarizations
- Larger reflector sizes as specifications may require
- 1435 to 2400 MHz frequency range

NOTES


¹Wider Frequency coverage available please consult Factory.

²G /T at 20° Elevation, 23° C, 7.5 gr/m³ and under clear sky conditions.


³Separate Data and Tracking channels and other feed configurations with

enhanced G/T performance are available as options.

Above specifications are with one LNA and no Band Pass Filter.



White Sands Missle Range



ViaSat, Inc. 1725 Breckinridge Plaza Duluth, GA 30096 Tel: +1.678.924.2400 Fax: +1.678.924.2480 www.yiasat.com

